

INDUSTRIAL FLEXIBLE DRUM HEATERS



Neptech Inc. produced drum heaters are thin, flexible electrical resistance heaters that can easily be wrapped and secured around drums, pails, and tanks. Every drum heater is made of silicone rubber-reinforced fiberglass cloth, laminated around a nickel alloy circuit. This construction provides an even heat transfer throughout.



FEATURES

- Fits four standard drum sizes
- Metal or non-metal drum versions
- 115V and 230V standard; high wattage 115V configuration available
- 3-prong plug or pigtail termination
- Electrically grounded insulation screen
- Optional adjustment thermostat
- Heavy hook and spring attachment
- Resistant to many chemical substances
- UL recognized and CSA Certified

TECHNICAL INFORMATION

Model Number	Fits Drum Size (gallon)	Drum Material	Wattage
IB-55	55	Metal	None
BXH-55-115-TS	55	Non-Metal	750
BXH-55-230-TS	55	Non-Metal	750
BH-55-115-TS	55	Metal	1000
BH-55-230-TS	55	Metal	1000
BHW-55-115-TS	55	Metal	1500
BHW-55-230-TS	55	Metal	1500

INDUSTRIES

- Biofuel
- Adhesives
- Mastics
- Paints and varnishes
- Oils, fats, and greases
- Epoxy and Resins
- Food and Beverage
- Tar Dispensing
- Spray Polyurethane Foam

INDUSTRIAL FLEXIBLE DRUM HEATERS

Metal Version Drum Heaters have the following prefixes: DH, DHW, DHH; Non-metal version Drum Heaters have the following prefix: XH,

Model Number	Drum Material	Drum Position	Fits Drum Capacity/ Diameter (gal./in.)	Total Wattage (W)	Voltage (V)	Adjustable Thermostat (°F)	Cord Termination	Length / Width (in.)
DH-5-115-TS	METAL	VERTICAL	5 / 11.25	300	115	50 to 425	3-prong plug	30 / 3
DH-15-115-TS	METAL	VERTICAL	15 / 14.25	500	115	50 to 425	3-prong plug	35.88 / 3
DH-30-115-TS	METAL	VERTICAL	30 / 18.25	750	115	50 to 425	3-prong plug	52.50 / 3
DH-55-115-TS	METAL	VERTICAL	55 / 22.5	1000	115	50 to 425	3-prong plug	64.50 / 3
DHW-5-115-TS	METAL	VERTICAL	5 / 11.25	450	115	50 to 425	3-prong plug	30 / 4
DHW-15-115-TS	METAL	VERTICAL	15 / 14.25	750	115	50 to 425	3-prong plug	35.88 / 4
DHW-30-115-TS	METAL	VERTICAL	30 / 18.25	1100	115	50 to 425	3-prong plug	52.50 / 4
DHW-55-115-TS	METAL	VERTICAL	55 / 22.5	1500	115	50 to 425	3-prong plug	64.50 / 4
DH-55-115	METAL	VERTICAL	55 / 22.5	1000	115	NONE	3-prong plug	64.50 / 8
DHH-55-115-TS	METAL	HORIZONTAL	55 / 22.5	500	115	50 to 425	3-prong plug	65.50 / 8
XH-5-115-Ts	NON-METAL	VERTICAL	5 / 11.25	300	115	50 to 160	3-prong plug	29 / 6
XH-15-115-TS	NON-METAL	VERTICAL	15 / 14.25	370	115	50 to 160	3-prong plug	38.5 / 6
XH-30-115-TS	NON-METAL	VERTICAL	30 / 18.25	590	115	50 to 160	3-prong plug	51 / 6
XH-55-115-TS	NON-METAL	VERTICAL	55 / 22.5	750	115	50 to 160	3-prong plug	64 / 6
DH-5-230-TS	METAL	VERTICAL	5 / 11.25	300	230	50 to 425	NONE	20 / 4
DH-15-230-TS	METAL	VERTICAL	15 / 14.25	500	230	50 to 425	NONE	35.88 / 4
DH-30-230-TS	METAL	VERTICAL	30 / 18.25	750	230	50 to 425	NONE	52.50 / 3
DH-55-230-TS	METAL	VERTICAL	55 / 22.5	1000	230	50 to 425	NONE	64.50 / 3
DHW-5-230-TS	METAL	VERTICAL	5 / 11.25	450	230	50 to 425	NONE	20 / 4
DHW-15-230-TS	METAL	VERTICAL	15 / 14.25	750	230	50 to 425	NONE	35.88 / 4
DHW-30-230-TS	METAL	VERTICAL	30 / 18.25	1100	230	50 to 425	NONE	35.88 / 4
DHW-55-230-TS	METAL	HORIZONTAL	55 / 22.5	1500	230	50 to 425	NONE	64.50 / 4
DHH-5-230-TS	METAL	HORIZONTAL	55 / 22.5	500	230	50 to 425	NONE	65.50 / 8
XH-5-230-TS	NON-METAL	HORIZONTAL	5 / 11.25	300	230	50 to 160	NONE	29 / 6
XH-15-230-TS	NON-METAL	HORIZONTAL	15 / 14.25	370	230	50 to 160	NONE	38.5 / 6
XH-20-230-TS	NON-METAL	HORIZONTAL	30 / 18.25	590	230	50 to 160	NONE	51 / 6
XH-55-230-TS	NON-METAL	HORIZONTAL	55 / 22.5	750	230	50 to 160	NONE	64 / 6